



ENVIRO STAIN

AQUA-GARD™

DESCRIPTION Sansin Aqua Guard™ is a clear, water protection product for new and existing above ground concrete and masonry substrates. Unlike regular water repellents Sansin Aqua-Guard™ penetrates and bonds to the substrate, allowing it to breath while protecting the concrete and masonry from water and contaminants entering the substrate.

APPLICATIONS

- Brick and Stucco Walls
- Concrete block buildings
- Concrete Structures, Roof tiles
- Concrete Slabs and sills, etc.

PRODUCT BENEFITS

- Clear, will not discolor
- Can be custom tinted
- Odorless
- Penetrates deep into the substrate
- Prevents freeze-thaw damage
- Reduces efflorescence, splitting & cracking
- Protects reinforcing steel from erosion
- Reduces dusting
- Breathable
- Keeps the substrate cleaner

CHARACTERISTICS

- Coloring
- Odor
- Form Liquid
- Specific Gravity (g/cm³)
- Density (lbs/gall)
- pH,.....
- Viscosity, @Zahn 4 @21°C
- Solvents.....
- Freezing Point
- Diluent
- Cleanup
- Drying Time (To touch) @ 20°C (68°F)...
.....Do not allow to dry
- Coverage(Depending on coating
appearance and thickness).....
..... 100-200 sqft/ Usgal
- Shelf life.....Looses
strength slowly over time
- VOC(g/l) 0 g/l

PACKAGING

Available in 1US gallon containers

COVERAGE

- Full saturation should be achieved.
- Will cover approximately 40-200sq.ft. per gallon dependant on porosity of the substrate.

PREPARATION

- Test Area: Pretest a hidden area. Check if surface has been pretreated. Appearance of a white residue after drying indicates a pretreated surface.

WORKING PROCEDURE

- Apply by sprayer, brush or roller
- Do not dilute
- Do not apply in heat of day or direct sunlight
- One coat application
- Can be applied at any temperature above freezing (ideal temperature between 15-20°C)
- Clean surface before application
- Apply liberally until the surface is saturated, do not allow to puddle.
- DO NOT SPILL ON ALUMINIUM WINDOWS ETC.
- Allow 28 days for new concrete to cure before treatment.
- See Directions For Use

STORAGE

- Close container lightly
- Store in cool dry
- Avoid exposure to sunlight
- Do not reuse container
- Do not allow freezing
- Rinse container thoroughly before disposal

SAFETY See Material Safety Data Sheet

WARNING TO USERS

Do not use metal containers.

The information contained in this document is given in good faith based on our current knowledge. The use of the product is beyond the control of The Sansin Corporation, and no guarantees, expressed

or implied, are made as to the result to be obtained if not used in accordance with the published Directions for Use. The Sansin Corporation does not assume any legal responsibility for use or reliance on same. This information must on no account be used as a substitute for necessary field tests, which alone can ensure that the product is suitable for the expected use. Before using any product, read its label.

September 2009