



SASCO PRODUCTS LIMITED

10 Ilsley Avenue, Unit 3, Dartmouth Nova Scotia Canada B3B 1L3

Telephone (902) 468-2126 Fax (902) 468-2642

www.sasco.ca

PRODUCT INFORMATION

BORACOL 10 - 2 BD

INORGANIC BORON WOOD PRESERVATIVE

INTRODUCTION

BORACOL 10 - 2 BD is a wood preservative which is mouldicidal, fungicidal and insecticidal; is fungicidal when used as a preventative treatment and highly effective in killing and preventing mould on wood and stone as well as other absorbent surfaces.

Precaution is to be taken when used where building material may be sensitive to surfactants.

SPECIAL PROPERTIES:

- . Very low mammalian toxicity
- . Very low vapour pressure (Negligible loss of active ingredient by evaporation)
- . Deep penetration into timber; even penetrates heartwood
- . Practically odourless and non-staining
- . Non-flammable
- . Wider spectrum of activity than conventional preservatives.

DESCRIPTION:

BORACOL 10 - 2 BD is a clear solution of 9.8% Disodium octaborate tetrahydrate and 2.0% didecyl dimethyl ammonium chloride in propylene glycol and water. It is designed for use as a surface treatment in-situ building material to prevent fungal attack and preserve against attack from both mould and wood boring insects. It penetrates 3 - 5mm into the wood and establishes a reserve from where further penetration takes place (40mm in 2 years has been demonstrated). It can also be used as an initial preventative treatment.

TECHNICAL DATA:

Active Substance

Disodium octaborate tetrahydrate 9.8% W/W ($\text{Na}_2 \text{B}_8 \text{O}_{13}, 4\text{H}_2\text{O}$)

Didecyl Dimethyl Ammonium Chloride (DDAC) 2.0%

Other Components

Contains propylene glycol

Safety Recommendations

Read Label and MSDS carefully before use.

Do not swallow. Protect eyes and skin. Wash thoroughly if contaminated by product.

Boracol 10-2 BD does not restore lost strength in wood.

Colour -- Colourless

Odour -- Very low

Flashpoint -- Above $>150^\circ\text{C}$

Fire and Explosion Hazard -- BORACOL 10 - 2 BD does not increase the ignition point of wood.

Corrosion

None, functions partly as a corrosion inhibitor. However may cause slight oxidizing of bare metals, especially aluminium!

Aggressivity to Other Materials

Does not attack glass, textiles, plaster, rubber, putty, mastics, sealants or paint systems.

Adhesive Application

Wood impregnated with BORACOL can be glued.

USES:

- As a surface treatment to prevent dry rot, wet rot and white rot in-situ building material.
- As a surface treatment to preserve existing and new timbers against fungal and insect attack.
- As a surface treatment to prevent mould growth, etc.

EXAMPLES OF PREPARATION:

Roof Timbers

Surface debris, dust and cobwebs must be removed and timbers thoroughly cleaned using an industrial vacuum cleaner. Insulation must be removed, water tanks and electrical junctions covered, ventilation ensured and common roof voids screened. Walking boards and safety lights should be installed.

Floor Timbers

Floor coverings must be carefully removed, timbers thoroughly vacuumed and sufficient access boards removed. Ventilation must be ensured without affecting adjacent areas with over spray.

Joinery

Painted architraves and skirtings must be removed or pried away from the wall and the unpainted surfaces cleaned.

APPLICATION:

BORACOL 10 - 2 BD may be applied by brushing, dipping, spraying to refusal, or by injection. Do not apply Boracol 10-2 BD when raining or extremely high humidity.

COVERAGE:

Rough sawn timber (brush)	1 litre to approx 3 m ² surface
Smooth prepared timber (brush)	1 litre to approx 3 - 4m ² surface
By spray (either surface)	1 litre to approx 3 - 4m ² surface
To prevent attacks	3 - 6 m ² / litre
To eradicate established attacks	2 - 3 m ² / litre
Mould and Fungi in wood	1m ² / litre*
Insect attacks 1m ² / litre*	* Divide between two applications

(If the wood is already attacked by fungi, mould or insects, it may absorb more per m²).

The Boric Acid equivalent is 1.2 times the amount of Boron in Boracol 10-2 BD (approx. 12% Boric Acid equivalent)

GENERAL DATA:

Cleaning

Ordinary tap water will clean tools, etc., equipment and spillages.

Packaging

1 litre, 4 litre, 20 litre and 200 litre plastic containers

Storage

Keep out of reach of children. Store in original containers, tightly closed an in a safe place. Keep away from food, drink and animal feedstuffs. Do not allow to freeze.

Shelf Life

6 - 12 months in cool, dry conditions.

HEALTH AND SAFETY:

BORACOL 10 - 2 BD is registered under the Pest Control Products Act, Registration Number: 25665 for use as a wood preservative. For commercial use only.

Acute Oral LD50 Oral Rats mg/kg	>2,000
Acute Dermal LD50 Rats mg/kg	>2,000
Acute LC50 Inhalation g/m ³	>8.9 g/m ³
Skin Irritation	Irritating
Eye irritation	May be irritating
Skin Sensitisation	May be sensitive

TECHNICAL ADVISORY SERVICE

Before determining the most appropriate product it is necessary to specifically identify the source of the problem, so that the best method of treatment can be applied. Technical advice of this nature is available from SASCO PRODUCTS LIMITED or your local Technical Agent.

This information given in good faith is based on many years experience and usage of similar products. However all recommendations and suggestions are made without prejudice, since the conditions of use are beyond our control. All goods are sold in accordance with our conditions of sale, copies of which are available on request.

SASCO PRODUCTS LIMITED
10 Ilsley Avenue, Unit 3
DARTMOUTH, NOVA SCOTIA B3B 1L3
CANADA
Telephone: (902) 468-2126 Fax: (902) 468-2642
www.sasco.ca