



SASCO Products Limited
distributor for...



A great product from GreenDolphin™ eco-solutions

FIRE SAFE 108 Wood... a ready-to-use, water-base intumescent fire retardant wood treatment. Formulated primarily for use as a Class A fire retardant treatment for fibrous cellulose material, **FIRE SAFE 108 Wood** also provides preservative and anti-bacterial properties.

Apply by brush, spray or dipping processes to a dry, oil free, dust free unfinished surface to allow FIRE SAFE 108 WOOD penetrate into the wood fibres. To achieve a ULC Class A rating, three coats of **FIRE SAFE 108 Wood** should be applied at a rate of 7.7m²/L per coat.

If any top coat to be used check compatibly.



Use FIRE SAFE 108 Wood to treat:

- Vertical and horizontal wood frames and studs
- Wooden roof deck and trusses
- Unsealed wall paneling
- Wooden stairways and hallways
- Base treatment for refinished surfaces
- Others

FIRE SAFE 108 Wood Features:

- Highly durable (can withstand over 1000 scrubbing cycles)
- Enhances wood lustre
- Complies with the standard method of testing for surfaces burning characteristics of building materials, CAN4-S102-M83
- Available as a wood stain
- Can be enhanced to provide excellent wood preservation and mildew resistant qualities for specific applications



WARRANTY: The manufacturer warrants that its products meet the specifications that it sets for them. The manufacturer makes no other warranties related to the product. The technical data furnished is true and accurate to the best of our knowledge, however no guarantee of accuracy is given or implied. We assume no responsibility for coverage, performance or injuries resulting from use. Maximum liability, if any is limited to replacement of products. Technical data are subject to change without prior notice

Read and observe all recommended safety and handling procedures when using this product.