



ENVIRO STAIN

WOOD SEALER

DESCRIPTION A premium water based, ultra low, water repellent for interior and exterior wood substrates. Wood Sealer is designed to bring dimensional stability to wood by reducing moisture absorption by up to 74% during wetting periods. Sansin Wood Sealer is guaranteed for 3 years (see limited warranty).

APPLICATIONS

Recommended for use on new and old wood surfaces such as decks, fences, siding, timbers and roofing shingles or shakes.

- Coverage, pending to penetration..... 100-200 sqft/ USgal
- Longer drying time needed in high humidity or low temperature
- Keep from freezing
- VOCg/L)Actual – 6
..... Regulatory - 64

PRODUCT BENEFITS

- VOC Compliant
- No Organic solvents
- Environmentally Sound
- Penetrates the substrate
- Reduces water absorption
- Reduces swelling of wood
- Water repellent
- Breathing
- Odorless
- Clear
- Non-slip surface coating
- Ready for application
- Clean up with soap and water

PACKAGING

Available in 1 and 5 US gallon plastic containers.

SURFACE PREPARATION

- Inspect wood surfaces for defects
- Clean the entire surface
- Sand the surface when possible to increase absorption
- Use only random orbital sanders and 60-80 grit paper

CHARACTERISTICS

- Appearance Hazy white
- Coloring Clear
- Odor Low
- Form Liquid
- Specific Gravity 1.00
- Density 8.3
- pH, (approx..)9-9.5
- Viscosity, Brookfield #1, 60RPM, 20°C (68°F)..... 5-6cPs
- Solvents..... None
- Freezing Point-1°C (31°F)
- Diluent Water
- Cleanup Water
- Drying Time @ 20°C (68°F) 48 Hours
- Drying Time(Between applications @ 20°C 68°F)..... 30 Minutes, not longer than 5 hours

APPLICATION METHODS

- Stir or shake before use
- Dipping
- Brushing
- Spraying
- Apply by flood coat
- A second coat must be applied 30 minutes to 1 our after the first coat was applied to a sanded surface for the warranty to take effect.

WORKING PROCEDURE

- Pretest at a hidden area
- Saturate the wood surface
- Brush out any puddles and runs
- Do not apply in heat of day or direct sun
- Do not apply on surfaces warm to the touch

- Do not dilute
 - Do not apply if rain or freezing temperature are expected
 - See published directions for use
-

STORAGE

Store at a temperature of between +2°C and +25°C (36°F and 77°F). Keep containers tightly closed.

SAFETY See Material Safety Data Sheet

WARNING TO USERS

Keep out of reach of children, if swallowed immediately drink two glasses of milk or warm water. Do not induce vomiting. Call physician immediately. Avoid contact with skin or eyes; flush

with soap and water. Avoid breathing of vapor or mist. Wear a properly fitted NIOSH approved respirator.

The information contained in this document is given in good faith based on our current knowledge. The use of the product is beyond the control of The Sansin Corporation, and no guarantees, expressed or implied, are made as to the result to be obtained if not used in accordance with the published Directions for Use. The Sansin Corporation does not assume any legal responsibility for use or reliance on same. This information must on no account be used as a substitute for necessary field tests, which alone can ensure that the product is suitable for the expected use. Before using any product, read its label.

February 2011